



# FortiGate-5000 - Hardware Compatibility Guide

FortiOS 6.4.1 FortiController 5.2.10

**FORTINET DOCUMENT LIBRARY**

<https://docs.fortinet.com>

**FORTINET VIDEO GUIDE**

<https://video.fortinet.com>

**FORTINET BLOG**

<https://blog.fortinet.com>

**CUSTOMER SERVICE & SUPPORT**

<https://support.fortinet.com>

**FORTINET TRAINING & CERTIFICATION PROGRAM**

<https://www.fortinet.com/support-and-training/training.html>

**NSE INSTITUTE**

<https://training.fortinet.com>

**FORTIGUARD CENTER**

<https://fortiguard.com/>

**END USER LICENSE AGREEMENT**

<https://www.fortinet.com/doc/legal/EULA.pdf>

**FEEDBACK**

Email: [techdoc@fortinet.com](mailto:techdoc@fortinet.com)



July 9, 2020

FortiGate-5000 Hardware Compatibility Guide FortiOS 6.4.1 FortiController 5.2.10

01-641-246510-20200709

# TABLE OF CONTENTS

<b>Change log</b> .....	<b>4</b>
<b>FortiGate-5000 chassis compatability</b> .....	<b>5</b>
<b>FortiGate and FortiController board hardware details</b> .....	<b>6</b>

# Change log

Date	Change description
July 9, 2020	Updated for FortiOS 6.4.1 and FortiController 5.2.10.
July 9, 2019	Updated for FortiOS 6.2.
August 11, 2017	Added the FortiGate-5001E and FortiGate-5001E1.
August 24, 2016	Corrected a few typos.
November 5, 2015	First Version.

# FortiGate-5000 chassis compatability

The following table lists the currently available FortiGate-5000 series chassis and the FortiGate and FortiController boards that are compatible with each. A FortiGate or FortiController board is supported in a chassis if the chassis can supply enough power and cooling for the board. Also taken into account is the fabric backplane speed of the chassis.

Chassis	Features	Supports
FortiGate-5144C	<b>Available power per slot:</b> 400W <b>Heat dissipation per slot:</b> 1535 BTU/hr <b>Fabric Backplane speed:</b> 40Gbps <b>Capacity:</b> 14 slots <b>Height:</b> 14U, 19-inch rack mount	All FortiGate, FortiSwitch, and FortiController boards.
FortiGate-5140B	<b>Available power per slot:</b> 300W <b>Heat dissipation per slot:</b> 1023 BTU/hr <b>Fabric Backplane speed:</b> 10Gbps <b>Capacity:</b> 14 slots <b>Height:</b> 14U, 19-inch rack mount	FortiGate-5001C, FortiGate-5101C, FortiGate-5001B, FortiController-5103B, FortiSwitch-5003B, FortiSwitch-5203B  FortiGate-5001D and FortiController-5902D (but only with 10Gbps fabric backplane support)
FortiGate-5060	<b>Available power per slot:</b> 300W <b>Heat dissipation per slot:</b> 1023 BTU/hr <b>Fabric Backplane speed:</b> 10Gbps <b>Capacity:</b> 6 slots <b>Height:</b> 5U, 19-inch rack mount	FortiGate-5001C, FortiGate-5101C, FortiGate-5001B, FortiController-5103B, FortiSwitch-5003B, FortiSwitch-5203B  FortiGate-5001D and FortiController-5902D (but only with 10Gbps fabric backplane support)

## FortiGate and FortiController board hardware details

The following table lists the interfaces, functions, power and cooling requirements of the currently available FortiGate and FortiController boards.

FortiOS 6.4.1 supports the following FortiGate boards ([FortiOS 6.4.1 release notes](#)):

- FortiGate-5001D
- FortiGate-5001E
- FortiGate-5001E1

FortiController 5.2.10 supports the following FortiController boards ([FortiController 5.2.10 release notes](#)):


- FortiController-5103B
- FortiController-5903C
- FortiController-5913C

ATCA board	Interfaces	Function	Power Used (W)*	Heat Dissipation (BTU/hr)*
<b>FortiGate-5001D</b>	<b>Front Panel:</b> 2 x 40 Gbps, 2 x 10 Gbps, or split into 8 x 10 Gbps <b>Fabric:</b> 40 Gbps or 10Gbps	FortiOS network security	Max: 226 Ave: 189	774
<b>FortiGate-5001E</b> <b>FortiGate-5001E1</b>	<b>Front Panel:</b> 2 x 40 Gbps, 2 x 10 Gbps, or split into 8 x 10 Gbps <b>Fabric:</b> 40 Gbps or 10Gbps	FortiOS network security	Max: 278 Ave: 250	948
<b>FortiController-5103B</b>	<b>Front Panel:</b> 8 x 10 Gbps, or 8 x 1 Gbps <b>Fabric:</b> 10 Gbps or 1 Gbps	Session-aware load balancing Clustering (SLBC) and FGCP HA	Max: 255 Ave: 213	754
<b>FortiController-5903C</b>	<b>Front Panel:</b> 4 x 40 Gbps or split into 16 x 10 Gbps <b>Fabric:</b> 40 Gbps or 10 Gbps	Session-aware Load Balancing Clustering (SLBC) and FGCP HA	Max: 400 Ave: 250	1360
<b>FortiController-5913C</b>	<b>Front Panel:</b> 2 x 100 Gbps or split into 20 x 10 Gbps <b>Fabric:</b> 40 Gbps or 10 Gbps	Session-aware Load Balancing Clustering (SLBC) and FGCP HA	Max: 400 Ave: 280	955

\*Approximate values, see product datasheets for official values.



**FORTINET**<sup>®</sup>



Copyright© 2020 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., in the U.S. and other jurisdictions, and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. In no event does Fortinet make any commitment related to future deliverables, features or development, and circumstances may change such that any forward-looking statements herein are not accurate. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.